





## J Press FP790

## Full Color Digital Press for Flexible Packaging

**FUJIFILM PACKAGING SOLUTIONS** 

In the field of flexible packaging, small lots, more SKUs, a wide variety of products and shorter delivery times are rapidly changing market dynamics. Achieving both high quality print and adhering to the regulatory requirements of the food packaging business, the J Press FP790 was created to meet these high market demands and enable a more strategic packaging business.

## J Press FP790 Features Include:

- · Water-based digital inkjet technology
- · High opacity white with two digital white inkjet channels
- New 1200x1200 dpi printing heads enabling highest quality printing
- Solid color density coverage & small font proficiency
- Hits 90%+ Pantone color gamut with CMYK
- · Higher productivity
- · Short lead times, quick delivery
- · Lower costs running short run jobs compared to flexo
- Easily execute personalization & regionalization
- Reduction of waste



PRINTING METHOD Water-based inkjet, single pass

PRINT SPEED 164 ft./min (50 m/min)

**IMAGE RESOLUTION** 1,200dpi x 1,200dpi

**MAXIMUM IMAGE SIZE** 29.6 in. (753mm)

**SUBSTRATE WIDTH** 20.5 – 31 in. (520mm – 790mm)

**SUBSTRATE THICKNESS** 12 to 40 microns

SUBSTRATE MATERIAL PET & BOPP

MAIN APPLICATION Flexible packaging for food and non-food, reverse print

**UN-WINDER**Max roll diameter: 23.6 in. (600mm), Max roll weight: 661lbs (300kg)

**RE-WINDER**Max roll diameter: 23.6 in. (600mm), Max roll weight: 661lbs (300kg)

**DIMENSIONS (W X H X D)**48 in. x 103 in. x 276 in. (1,209mm x 2,615mm x 7,000mm)

**WEIGHT** 52,911 lbs. (24,000kg)

**MINIMUM FLOOR SPACE (W X D)** 634 in. x 317 in. (16,090mm x 8,060mm)

incl. auxiliary equipment & work space

POWER-SUPPLY VOLTAGE 200V and 400V

**INK** Water-based pigmented ink, 5 colors

WP-F Cyan, Magenta, Yellow, Black and White

PRE-CONDITIONER Water-based coating liquid

## **FUJ!FILM**

FUJIFILM North American Corporation, Graphic Systems Division

FujifilmGraphics.com | 800.877.0555 | contactgraphics@fujifilm.com

Specifications are subject to change without notice. The name FUJIFILM and the FUJIFILM logo are trademarks for FUJIFILM Corporation. All other trademarks shown are trademarks of the owners. All rights reserved.